

WALLMOUNT ENCLOSURES

Outdoor Type (IP65/IP66) IK10

PAINT : RAL7035W Electrostatic Powder Coating

GASKET : Poliuretan Liquid Gasket

PROTECTION : IP65/IP66 (Outdoor Type) - IK10

AVAILABLE DIMENSION : Width: 300-800mm Height: 400-1200mm Depth: 150-300mm

DOOR : Quarter Turn - Spring Loaded Locks and Corner Hinge or Concealed Hinge
Front door can be open up to 180°

MATERIAL:

Cargass : 1,0 mm<1000≤ 1,2 mm painted steel

Door :1,0 mm<1000≤ 1,2 mm painted steel

Mounting Plate : 1,0 mm<1000≤ 1,2 mm galvanized steel

Internal Parts: 1,2 mm<1000≤ 1,5 mm galvanized steel

Cover Plate:1,0 mm painted steel

OPTIONS : The enclosures have the ability to use both mounting plate and interior covers in the same body. No need to change the enclosure for different applications.

BODY : Welded type. Four 7.5 mm diameter holes for wall fixing at the rear part of the enclosure.

MOUNTING PLATE : Supplied as an accessory with multiple size options.

CERTIFICATES : CE, IEC,TSE,ISO,GOST.